



5CCT ULTRA SLIM PANEL WITH NIGHT LIGHT



DESCRIPTION

LED Ultra-thin night light is a fixture with modern technology, ultra-thin lamp body, and also have night Light function . It is suitable for bedrooms, kitchens, hallways ,etc.

3" 4" 6" 8"

FEATURES

- Soft amber hue when night light mode activated
- Without recessed cans or a separate j-box
- CRI 90 for true color rendering
- No flicker

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed. FCC.

BASED ON SAMPLE SETTING.ACTUAL LUMENS MAY VARY.

<i>MODEL #</i>	<i>MAIN LIGHT WATTAGE</i>	<i>LUMEN</i>	<i>NIGHT LIGHT WATTAGE</i>
3EJCT06SR05-N	6W	390Lm	3W
4EJCT09SR05-N	9W	630Lm	3W
6EJCT12SR05-N	12W	1000Lm	3W
8EJCT18SR05-N	18W	1400Lm	3W

TECHNICAL SPECIFICATION

VOLTAGE	120V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
MAIN LIGHT CCT	2700K 3000K 3500K 4000K 5000K
NIGHT LIGHT CCT	2000K
CRI	90
BEAM ANGLE	120°
MATERIAL	Al+PC
LIFESPAN	≥50,000hours
OPERATING TEMP	(-4°F~ 113°F) -20~45°C
DIMMABLE	Triac Dimmable
RATING	Suitable for Wet Locations
WARRANTY	5 years Limited



1. Selecting main light mode or night light mode

The product has two modes: main light mode and night light mode. Main light mode provides full brightness and allows selection from five color temperatures: 2700K, 3000K, 3500K, 4000K and 5000K. Night light mode provides reduced light output at 2000K color temperature for very soft illumination at night

Daily mode

2. Convenient control using light switch

Switch the downlight off and back on again within (1-4) seconds to activate night light mode. NOTE: The main downlight will not provide light output when the night light trim is illuminated.

Night light mode

RECOMMENDED DIMMER

LUTRON						LEVITON	
CT-600PR-WH CTCL-153PDH- WH TGCL-153PH-LA	SLV-600PAL GT-600P DVCL-153P	MSCL-OP153M PD-6WCL S2-LFSQH-WH	CT-103PR-WH STCL-153MR MACL- 1153//MA-R	DVWCL-153PH RCL-153RNL	DVRF-6L CTCL-150H	6672 6674	RNL06 IPL06

SIZE & DIMENSION & HOLE CUTOUT

Size	Dimension	Hole Cutout
3inch		 $\Phi 3 \frac{5}{64}'' (78\text{mm})$
4inch		 $\Phi 4 \frac{21}{64}'' (110\text{mm})$
6inch		 $\Phi 6 \frac{19}{64}'' (160\text{mm})$
8inch		 $\Phi 8 \frac{5}{64}'' (205\text{mm})$