



5CCT ROUND SLIM PANEL



DESCRIPTION

Ultra slim design, lamp thickness only 0.39".

Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K.

IC rated for direct contact with insulation. Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms.

3" 4" 6" 8" 12"

FEATURES

- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many Triac Dimmers
- Instant on

INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

LISTING

ETL Listed. Energy Star. FCC.Title24.

BASED ON SAMPLE SETTING.ACTUAL LUMENS MAY VARY.

| MODEL # | SIZE | WATTAGE | 5CCT | LUMENS |
|---------------------|-------------|----------------|-------------|---------------|
| KOK- 3EJCT06SR05 | 3Inch | 6W | 2700K | 430Lm |
| | | | 3000K | 460Lm |
| | | | 3500K | 480Lm |
| | | | 4000K | 500Lm |
| | | | 5000K | 470Lm |

| MODEL # | SIZE | WATTAGE | 5CCT | LUMENS |
|---------------------|-------------|----------------|-------------|---------------|
| KOK- 4EJCT09SR05 | 4Inch | 9W | 2700K | 650Lm |
| | | | 3000K | 750Lm |
| | | | 3500K | 750Lm |
| | | | 4000K | 760Lm |
| | | | 5000K | 680Lm |

| MODEL # | SIZE | WATTAGE | 5CCT | LUMENS |
|---------------------|-------------|----------------|-------------|---------------|
| KOK- 6EJCT12SR05 | 6Inch | 12W | 2700K | 850Lm |
| | | | 3000K | 930Lm |
| | | | 3500K | 990Lm |
| | | | 4000K | 1010Lm |
| | | | 5000K | 950Lm |

| MODEL # | SIZE | WATTAGE | 5CCT | LUMENS |
|-----------------|-------------|----------------|-------------|---------------|
| KOK-6EJCTI5SR05 | 6Inch | 15W | 2700K | 1200lm |
| | | | 3000K | 1290Lm |
| | | | 3500K | 1350Lm |
| | | | 4000K | 1360Lm |
| | | | 5000K | 1340Lm |

| MODEL # | SIZE | WATTAGE | 5CCT | LUMENS |
|-----------------|-------------|----------------|-------------|---------------|
| KOK-8EJCTI8SR05 | 8Inch | 18W | 2700K | 1300Lm |
| | | | 3000K | 1430Lm |
| | | | 3500K | 1570Lm |
| | | | 4000K | 1570Lm |
| | | | 5000K | 1440Lm |

| MODEL # | SIZE | WATTAGE | 5CCT | LUMENS |
|------------------|-------------|----------------|-------------|---------------|
| KOK-12EJCT24SR05 | 12Inch | 24W | 2700K | 1870Lm |
| | | | 3000K | 1950Lm |
| | | | 3500K | 2010Lm |
| | | | 4000K | 2010Lm |
| | | | 5000K | 1900Lm |

TECHNICAL SPECIFICATION

| | |
|------------------------|---------------------------------------|
| VOLTAGE | 120V |
| POWER FREQUENCY | 60Hz |
| POWER FACTOR | >0.9 |
| 5CCT | 2700K 3000K 3500K 4000K 5000K |
| CRI | 90 |
| BEAM ANGLE | 120° |
| MATERIAL | PS+AL |
| COLOR | White |
| LIFESPAN | ≥50,000hours |
| OPERATING TEMP | (-4°F~ 113°F) -20~45°C |
| DIMMABLE | Triac dimming |
| RATING | Suitable for Wet Locations |
| WARRANTY | 5 years Limited |

Easily flip the switch for desired CCT



SIZE & DIMENSION & HOLE CUTOUT

| | | | |
|----------------------|--|--|---|
| <p>3inch</p> | | | <p>Hole Size</p> <p>Φ3 5/64" (78mm)</p> |
| <p>4inch</p> | | | <p>Hole Size</p> <p>Φ4 21/64" (110mm)</p> |
| <p>6inch</p> | | | <p>Hole Size</p> <p>Φ6 19/64" (160mm)</p> |
| <p>8inch</p> | | | <p>Hole Size</p> <p>Φ8 5/64" (205mm)</p> |
| <p>12inch</p> | | | <p>Hole Size</p> <p>Φ11 1/32" (280mm)</p> |

RECOMMENDED DIMMER

| LUTRON | | | | LEVITON | |
|----------------|---------------|--------------|-----------------|---------|-------|
| TG-600PR-WH | TGCL-153PH-LA | SCL-153PH-WH | MSCL-OP153M | 6672 | |
| S-600PR-WH | SLV-600P-AL | DVCL-153P | MACL-153M//MA-R | 6674 | RNL06 |
| CTCL-153PDH-WH | DV-600PR-WH | | PD-6WCL | DSL06 | IPL06 |

ACCESSORIES



J-Box driver



Connector



Hole cutout card